



## PRODUCT

## ALUMAT 10 D (Draining)

### DESCRIPTION

Heavy duty aluminium and infill entrance mat with water draining channels

### USES

Mat depth 10mm. Install in set downs 8 – 12mm deep or on flat level surfaces with prefitted ramping

### FEATURES

Infill width 30mm alternating with water drain channels. For use both in covered weather protected areas or exposed positions where draining or evaporation channels are required. Variable depth FULL rubber base instead of strips provides uniform cushioning and weight distribution with no 'clatter' or distortion.

Fully interlocking allows for complex mat shapes and can be seamlessly joined to make any width or depth mats.

Choose from our range of colour infills, or rubber scraper bars.

### LIMITATIONS

Our standard heavy duty infills and frames are guaranteed 5 years. For guaranteed extended frame life (10 years minimum) we recommend the ALUMAT HD profiles eg 10 WD (Wide Draining), but we will refurbish Alumat 10 D if suitable after the guarantee period has expired.

Substrates must be properly prepared and level as per our specifications available on our website.

### PERFORMANCE

Complies with all Australian and New Zealand building code requirements, including the following:

EN ISO 9239-1 Critical Flux  $\geq 8$  kw/m<sup>2</sup>

Slip test compliant in both wet and dry situations. AS/NZS3661.1

### MATERIALS

Infills 100% air-entangled polypropylene with FR backing ( fire retardant) made by leading Dutch manufacturer, Vebe Floor Coverings for distribution in New Zealand exclusively by Alumat Flooring Solutions.

1720g/m<sup>2</sup>, pile thickness 4mm, O/A height 10mm.

Base frames are made from exterior grade satin anodised 6063-T5 magnesium alloy

Fully rubber backed ensures clatter-free operation and comfort underfoot.

### WATER ABSORPTION

Alumat rib infill is impervious to water by design, offering a superior way of dealing with In-coming dirt and water. The rigid polypropylene ribs scrape footwear and collect water and dirt in the troughs, keeping them away from shoe contact. Water evaporates, and as the non-absorbent fibres are stain resistant, they are easier to clean and stay looking clean for longer. Incorporating the drain channels allows for increased water collection or drainage.

### GUARANTEE

ALUMAT AL10 D has a 5 year warranty on both frames and infills subject to reasonable wear and tear.

### PRICE INDICATION

As at June 2017, ALUMAT AL10 D is priced at \$499 per sq.m plus GST. (NZ freight free)

***Alumat Flooring Solutions Data sheet 10 D 1/6/17***