




P. +64 9 473 1602, 0800 ALUMAT
 F. +64 9 473 8406
 E. info@alumat.co.nz
 W. www.alumat.co.nz

PRODUCT

ALUMAT 10 WD (Wide Draining)

DESCRIPTION

Extra heavy duty aluminium and infill entrance mat with water draining channels

USES

Mat depth 10mm. Install in set downs 8 – 12mm deep or on flat level surfaces with prefitted ramping

FEATURES

Infill width 50mm alternating with water drain channels for use both in covered weather protected areas or exposed positions where draining or evaporation channels are required. Water is taken away for the mat surface, rather than holding and releasing again by pressure of foot traffic. Ezi-clean with no under mat soiling.

Variable FULL rubber base instead of strips, and extra thick aluminium provides uniform cushioning and weight distribution with no ‘clatter’ or distortion.

Fully interlocking allows for complex mat shapes and can be seamlessly joined to make any width or depth mats.

These extra heavy frames have a 10 year warranty, which means we guarantee the frames can be refurbished with new infills to look and perform like new for the first ten years.

Choose from our range of colour infills.

LIMITATIONS

Substrates must be properly prepared and level as per our specifications available on our website.

PERFORMANCE

Complies with all Australian and New Zealand building code requirements, including:

EN ISO 9239-1 Critical Flux ≥ 8 kw/m²

Slip test compliant in both wet and dry situations. AS/NZS3661.1

MATERIALS

Infills 100% air-entangled polypropylene with FR backing (fire retardant) made by leading Dutch manufacturer, Vebe Floor Coverings for distribution in New Zealand exclusively by Alumat Flooring Solutions.

1720g/m², pile height 10mm.

Base frames are made from exterior grade satin anodised 6063-T5 magnesium alloy

Fully rubber backed ensures clatter-free operation and comfort underfoot.

WATER ABSORPTION

Alumat rib infill is impervious to water, offering a superior way of dealing with In-coming dirt and water. The rigid polypropylene ribs scrape footwear and collect water and dirt in the troughs, keeping them away from shoe contact. Water evaporates, and as the non-absorbent fibres are stain resistant, they are easier to clean and stay looking clean for longer. Incorporating the drain channels allows for increased water collection or drainage.

GUARANTEE

ALUMAT AL10 HD DW has a 5 year warranty on infills subject to reasonable wear and tear, and a 10 year suitable-for-refurbishment warranty on the extra heavy duty frames.

PRICE INDICATION

As at June 2017, ALUMAT AL10 HD DW is priced at \$519 per sq.m plus GST. (NZ freight free)

Alumat Flooring Solutions Data sheet 10 WD 1/6/17