

## CONTACT

Alumat Flooring Solutions

PO Box 89-018, Torbay,  
Auckland 0742.

Phone +64 9 473 1602

0800 258 628

Web : [www.alumat.co.nz](http://www.alumat.co.nz)

E: [info@alumat.co.nz](mailto:info@alumat.co.nz).

# DATA SHEET Alumat 10 W Jan 2024

## Manufacturer

Alumat Flooring Solutions (Probett Developments Ltd)

## Product Description

Ultra-low aluminium and infill entrance matting system. Heavy duty wearing polypropylene inserts

## Product Features

Extra wide infill strip

Fully rubber backed for clatter-free operation. Shrink-proof easy to clean infills. Safety is assured with Interlocking design that is heel-proof and fully safety compliant.

## Where to use?

Use in busy entrances requiring a product that will last and retain it's appearance. Suitable for shops, schools, hotels, office buildings etc. The integral screw-free aluminium ramping option enables placement on polished concrete, or adjacent to other low height floor coverings without the need of a mat-well.

## Dimensions

### Depth

Aluminium	8mm.
Infill	10mm

### Width

Infill strip	50mm
Overall profile	56mm

## Finishes

Satin silver anodizing.

5 infill colour options. Black, silver, red, sisal and brown.

## Safety compliance

Tested and exceeds all relevant fire safety standards in New Zealand and Australia EN ISO 9239-1

Slip test compliant in both wet and dry situations. AS/NZS3661.1

## Materials

Exterior grade 6063-T5 aluminium.

Fire retardant backed heavy duty loop pile infill, specially formulated by Vebe in the Netherlands for heavy use entrance ways.

## Installation

For maximum life, our mats must be installed on hard, level surfaces by suitably qualified tradesmen.

See Installation instructions

## Cleaning

To ensure long product life, our mats should be cleaned regularly.

See Cleaning Instructions.

## Water Absorption

Alumat rib infill is impervious to water, providing a superior way of dealing with incoming water and dirt. Rigid polypropylene ribs scrape footwear and collect water and dirt in troughs, keeping them away from shoe contact.

The non-absorbent fibres being stain resistant are easier to clean and stay looking clean for longer.

## Warranty

Alumat aluminium frames are warranted for 5 years ( Alumat 10 I, 10 D, & 10 DO.)

10 years (Alumat 10 W, 10 WD, & 10 WDO) & 20 Years (Alumat 15 I, 15 D 15 DO and 15 WD)

Infills are warranted for 5 years., and can be replaced to extend the mat life.