

CONTACT

Alumat Flooring Solutions
PO Box 89-018, Torbay,
Auckland 0742.
Phone +64 9 473 1602
0800 258 628
Web : www.alumat.co.nz
E: info@alumat.co.nz.

DATA SHEET Alumat 10 DO Jan 2024

Manufacturer

Alumat Flooring Solutions (Probett Developments Ltd)

Product Description

Ultra-low aluminium and infill entrance matting system. Heavy duty wearing polypropylene inserts

Product Features

Alternating infill and drop through water collection channels for use as part of a water removal system

Fully rubber backed for clatter-free operation. Shrink-proof easy to clean infills. Safety is assured with Interlocking design that is heel-proof and fully safety compliant.

Where to use?

Use in busy entrances requiring a product that will last and retain it's appearance. Suitable for shops, schools, hotels, office buildings etc. The integral screw-free aluminium ramping option enables placement on polished concrete, or adjacent to other low height floor coverings without the need of a mat-well.

Dimensions

Depth

Aluminium	8mm.
Infill	10mm

Width

Infill strip	28mm
Overall profile	48 mm

Finishes

Satin silver anodizing.

5 infill colour options. Black, silver, red, sisal and brown.

Safety compliance

Tested and exceeds all relevant fire safety standards in New Zealand and Australia EN ISO 9239-1

Slip test compliant in both wet and dry situations. AS/NZS3661.1

Materials

Exterior grade 6063-T5 aluminium.

Fire retardant backed heavy duty loop pile infill, specially formulated by Vebe in the Netherlands for heavy use entrance ways.

Installation

For maximum life, our mats must be installed on hard, level surfaces by suitably qualified tradesmen.

See Installation instructions

Cleaning

To ensure long product life, our mats should be cleaned regularly.

See Cleaning Instructions.

Water Absorption

Alumat rib infill is impervious to water, providing a superior way of dealing with incoming water and dirt. Rigid polypropylene ribs scrape footwear and collect water and dirt in troughs, keeping them away from shoe contact.

The non-absorbent fibres being stain resistant are easier to clean and stay looking clean for longer.

Warranty

Alumat aluminium frames are warranted for 5 years (Alumat 10 I, 10 D, & 10 DO.)

10 years (Alumat 10 W, 10 WD, & 10 WDO) & 20 Years (Alumat 15 I, 15 D 15 DO and 15 WD)

Infills are warranted for 5 years., and can be replaced to extend the mat life.