DATA SHEET Alumat Modul Jan 2024

Manufacturer

Alumat Flooring Solutions (Probett Developments Ltd)

Product Description

Modul is a low profile modular matting system, ideally used adjacent to other low height floor coverings such as tiles, carpet etc. without the need for a mat-well. It can also be placed on hard flat surfaces incorporating the Modul ramping system.

Product Features

The interlocking assembly is ideally used in large interior areas, or irregular shaped areas.

Simply install the whole tiles and trim the perimeter tiles as needed.

The walking surface is comprised of alternating ribbed infill strips, rigid scraper bars and water collection channels to effectively keep interiors clean and dry. There are no air cavities which enables Modul to withstand heavy rolling loads.

Where to use?

Use in busy entrances requiring a product that will last and retain it's appearance. Suitable for shops, schools, hotels, office buildings etc.

Dimensions

Depth 10mms

Tile size 500mm x 250mm

Finishes

The tile base is made from PVC and the the infills are heavy duty ribbed Polypropylene.

5 infill colour options. Black, silver, red, sisal and brown.

Tile PVC base standard colour is black, but other colours may be supplied on request.

Safety compliance

Tested and exceeds all relevant fire safety standards in New Zealand and Australia EN ISO 9239-1

Slip test compliant in both wet and dry situations. AS/NZS3661.1

Materials

Fire retardant backed heavy duty loop pile infill, specially formulated by Vebe in the Netherlands for heavy use entrance ways.

Installation

For maximum life, our mats must be installed on hard, level surfaces by suitably qualified tradesmen.

See Installation instructions

Cleaning

To ensure long product life, our mats should be cleaned regularly.

See Cleaning Instructions.

Water Absorption

Alumat rib infill is impervious to water, providing a superior way of dealing with incoming water and dirt. Rigid polypropylene ribs scrape footwear and collect water and dirt in troughs, keeping them away from shoe contact. The non-absorbent fibres being stain resistant are easier to clean and stay looking clean for longer. **Warranty**

Modul has a 5 year warranty subject to manufacturers installation and maintenance instructions being adhered to , and fair wear and tear.

CONTACT

Alumat Flooring Solutions PO Box 89-018, Torbay, Auckland 0742. Phone +64 9 473 1602 0800 258 628 Web : www.alumat.co.nz E: info@alumat.co.nz.