

DATA SHEET Alumat Modulock 15 Jan 2024

Supplier

Alumat Flooring Solutions (Probett Developments Ltd)

Product Description

Interlocking carpet entrance tiles to keep interior floor surfaces clean and dry

Zoned for pedestrian traffic as well as heavy duty wheeled traffic. Ideally used in Shopping Malls for quick and easy installation in large and irregular shaped entry ways.

Modulock15 has proven itself to be extremely durable and maintains its appearance well. See 'Our Work'

Glenfield Shopping Mall. Modulock 15 was installed in this busy Mall at all entrance ways over 5 years ago, and the mats continue to perform and look great with no repairs ever being required.

Modulock 15 is a cost effective alternative to other similar products..

Product Features

Simply install the whole tiles and trim the perimeter tiles as needed.

Where to use?

Use in busy entrances requiring a product that will last and retain it's appearance. Suitable for shops, schools, hotels, office buildings etc.

Dimensions

Depth

Tile height	12.5mms
Product height	14mms
Tile size	29cm x 44cm

Finishes

The tile base is made from PVC and the the infills are heavy duty ribbed Polypropylene.

Colours are either grey or charcoal.

Safety compliance

Tested and exceeds all relevant fire safety standards in New Zealand and Australia EN ISO 9239-1

Slip test compliant in both wet and dry situations. AS/NZS3661.1

Materials

Fire retardant backed infill, specially formulated by Vebe in the Netherlands for high use entrance ways.

Installation

For maximum life, our mats must be installed on hard, level surfaces by suitably qualified tradesmen.

See Installation instructions

Cleaning

To ensure long product life, our mats should be cleaned regularly.

See Cleaning Instructions.

Water Absorption

Alumat infill is impervious to water, providing a superior way of dealing with incoming water and dirt. Rigid polypropylene ribs scrape footwear and collect water and dirt in troughs, keeping them away from shoe contact.

The non-absorbent fibres being stain resistant are easier to clean and stay looking clean for longer.

Warranty

Modulock15 has a 5 year warranty subject to manufacturers installation and maintenance instructions being adhered to , and fair wear and tear.

CONTACT

Alumat Flooring Solutions

PO Box 89-018, Torbay,

Auckland 0742.

Phone +64 9 473 1602

0800 258 628

Web : www.alumat.co.nz

E: info@alumat.co.nz.